

| FEATURES | M Series |
|-------------------------|---|
| Physical pitch | P55mm |
| Pixel Composition | 3 in 1 SMD 3535 |
| Pixel Matrix per Panel | 8 (h) x 90 (w) dots |
| Pixel Density per Panel | 720 dots |
| Panel Size | 1.45 ft x 16.24 ft = 23.458 sq ft 441.96mm x 4949.95mm = 2.188 SQM |
| Weirght per Panel | 8.75 KG 19.29 Lbs |
| Brightness | 1000 nits |
| Transparency | 65% |
| Refresh Rate | ≥1000Hz |
| Gray Scale | 12 bit |
| Color Space | 16.7Million / 68.7 Billion |
| Brightness Adjustment | 256 Level |
| Viewing Angle | 120°(H)/120°(V) |
| Controller | Aynchronous system, or Synchronous display with control PC by DVI |
| Environment | Temperature -30 ~+45 Humidity 10~90% RH |
| IP Rating | IP65 w/ LED Panel IP54 w/ Signal distributor & power box |
| Power Input | AC110~ 240V, 50/60Hz |
| Operating Life | 100,000 HOURS |
| Max. Power Consumption | 150 W/m ² |
| Avg .Power Consumption | 75 W/m ² |