

Model	P3.75-6.66	P3.75-8	P5-6.66	P5-8	P7.5-8	P10	P16	P20
Pixel Pitch	3.75	3.75	5	5	7.5	10	16	20
Scanning Mode	1/8	1/8	1/6	1/6	1/4	1/3	1	1
Pixel Density	40,000 dots/m2	33,333 dots/m2	30,000 dots/m2	25,000 dots/m2	16,667 dots/m2	10,000 dots/m2	3,906 dots/m2	2,500 dots/m2
Pixel Configuration	1921	1921	3528	3528	3528	3528	3528	3528
Module Resolution	128 x 48	128 x 40	96 x 48	96 x 40	64 x 40	48 x 32	30x 20	20 x 16
Module Size	480 x 320							
Cabinet Size	960 x 640							
Cabinet Resolution	256 x 96	256 x 80	192 x 96	192 x 80	192 x 80	96 x 64	60 x 40	40 x 32
Brightness	5500 - 6000 nits							
Refresh Rate	>1920 Hz							
Transparency Rate	72%	75%	72%	75%	75%	80%	83%	86%
Weight (kg/m2)	11 kg	10.2 kg	10 kg	9.5 kg	9 kg	8 kg	7.2 kg	6.5 kg
Viewing Angle	140* (H) x 140* (V)							
Power Consumption	690/207 W/m2	670/201 W/m2	696/209 W/m2	670/203 W/m2	670/204 W/m2	650/195 W/m2	650/218 W/m2	650/218 W/m2