

Model	E III M-6.6	E III M-8	E III M-10	E III M-16	E III M-20
Pixel Pitch	6.67mm	8mm	10mm	16mm	20mm
Pixel Configuration	SMD			DIP	
Application	outdoor				
<b>Module Information</b>					
Resolution of Module (HxW)	48x72	40x60	32x48	20x40	16x32
Size of Module (mm) (HxW)	320x480			320x640	
<b>Display Information</b>					
Standard Cabinet Size (mm) (front access)	1280x1440x100			1280x1920x110	
Standard Cabinet Size (mm) (back access)	1280x960x105			1280x1280x115	
Power Consumption Max.(W/m <sup>2</sup> )	750			480	
Power Consumption Avg.(W/m <sup>2</sup> )	250			168	
Weight (kg/m <sup>2</sup> )	25.5				
Brightness (cd/m <sup>2</sup> )	7500			6500	
Contrast Ratio	5000:1				
Viewing Angle	170°/ 170°				
IP Rating	Front: IP67 Back: IP66				
Grey Level	16Bit				
Frame Frequency (Hz)	60				
Refresh Frequency (Hz)	1920				
Brightness Control	Manual / Auto / Scheduled				
Operating Temp / Humidity	-30°C~60°C / 10%~90%				