

Model	VFI1.9LTXR	VFI2.6LTXR	VFI3.9LTXR
Pixel Pitch	1.95mm	2.6mm	3.9mm
Size of Cabinet (W x H - mm)	500 x 1000 x 62 (customizable options)		
Resolution of Cabinet (W x H - pixels)	256x512	192x384	128x256
Weight of Cabinet (KG)	16.4		
Size of Module (W x H - mm)	250 x 250		
Resolution of Module (W x H -pixels)	128 x 128	96 x 96	64 x 64
Pixel Configuration	3 in 1 SMD 1010 True Black		
Grey Level	20 Bit		
Refresh Frequency	>4800HZ on MSB and LSB Grey scale and special proprietary cross scanning technology.		
White Balance Brightness at 6500K after Calibration	1500 Nits	1200 Nits	
Color Temperature	3200K to 9500K (4 x Presets and 1 Custom)		
Viewing Angle	>= 170° / 170°		
Maintenance Access	Rear (Front Access Optional)		
Voltage	110/220VAC, 50-60HZ		
Operating Temp / Humidity	-20°C - 65°C / 10%-85%		
Typical Lifetime	>= 100 000 hrs MTBF 25 000 hrs		
Power Consumption of Cabinet Max. (W/m²)	450		
Power Consumption of Cabinet Avg. (W/m²)	160		